

☆☆☆ 237 Series ☆☆☆

P/N: H271S0200C-3N

Material: Nylon 6/6, UL 94V-2

Conductor: Phosphor Bronze, Tin-Plated

Wire Range: AWG #22~#28

Available: 2~24P

Current Rating: 3A AC/DC

Voltage Rating: 250V AC Max.

Contact Resistance: Initial value/10mΩ Max.

After environmental testing/20mΩ Max.

Insulation Resistance: 1000MΩ Min.

Dielectric Strength: 1500V AC/minute




Operating Temperature range: -40°C~105°C

REVISIONS



REV	DESCRIPTION	DATE	DRAWN
A			

C	Color	Wire #
2	Red	#22
9	White	#24
6	Blue	#26
5	Green	#28




H271S**00C-1N






H271S**00C-2N



H271S**00C-3N



H271S**00C-4N



Circuitis	Dim. A	Dim. B	13	30.48	33.02
2	2.54	5.08	14	33.02	35.56
3	5.08	7.62	15	35.56	38.10
4	7.62	10.16	16	38.10	40.64
5	10.16	12.70	17	40.64	43.18
6	12.70	15.24	18	43.18	45.72
7	15.24	17.78	19	45.72	48.26
8	17.78	20.32	20	48.26	50.80
9	20.32	22.86	21	50.80	53.34
10	22.86	25.40	22	53.34	55.88
11	25.40	27.94	23	55.88	58.42
12	27.94	30.48	24	58.42	60.96

RoHS Compliant



C&J Connector

TEL: 886-2-86871898

FAX: 886-2-86872959

Mail: tceldh@gmail.com

Web: http://www.cnj.tw/

TITLE

.100"(2.54mm) Housing with Locking Ramp
Feed-Thru and Closed End Type

DIMENSION TOLERANCE

.x ±0.30 x° ±2°

.xx ±0.20

.xxx ±0.10

P/N	H271S**00C-*N	CHECKED	David	UNIT	mm	DATE	2010/11/26
DRAWN	Michael	APPROVED	Lily	SCALE	1:1	REV	A